

CORE RANGE

FIRECHIEF®
making the world a safer place

FIRECHIEF CTX 2L SPRAY FOAM EXTINGUISHER

This Firechief CTX Foam Extinguisher is an excellent solution for multi-risk usage. Ideal for use on A class fires (wood/paper) and B class (petrol & volatile liquids), the foam forms a flame smothering seal to prevent reignition.

MODEL:
CXF2 CTX

- Kitemark certified to BS EN 3
- 5 year guarantee
- 35kV dielectric test
- Squeeze grip operation
- Internal polyethylene lining
- Spray nozzle
- Corrosion resistant finish
- Complete with bracket



CXF2
100-1674

Specifications

| | |
|------------------------|------------------------------------|
| Model | CXF2 |
| Product Code | 100-1674 |
| Description | Firechief CTX 2L Foam Extinguisher |
| Capacity (l) | 2 |
| Fire Rating | 5A 55B |
| Discharge Time (secs) | 20 |
| Working Pressure (bar) | 15 |
| Temperature Range (°C) | +5 to +60 |
| Product Height (mm) | 370 |
| Product Diameter (mm) | 110 |
| Filled Weight (kg)* | 3.6 |
| Carton Height (mm) | 400 |
| Carton Length (mm) | 100 |
| Carton Width (mm) | 100 |
| Packaged Weight (kg)** | 4 |
| Product EAN | 5055377963934 |

* Extinguisher, contents and plastic base only (where applicable) - not including hose, bracket or packaging.
** Includes all packaging, hose / horn and bracket.



KM 95424
BS EN 3



For more information contact: Firechief Global, 3 Lands End Way, Oakham, Rutland, UK, LE15 6RB | Imported into EU by: Firechief Global (EU) Ltd, 3rd Floor, 40 Mespil Rd, Dublin 4, Ireland, D04 C2N4



+44 (0) 330 999 0019



sales@firechiefglobal.com



firechiefglobal.com

V2_23/01/24